

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) Log-cabin type ~~façade~~ facade for cladding walls in internal and external areas with at least one elongated contoured element for cladding a wall surface, which are arranged over each other, with corner-forming elements that are assigned to the contoured elements and are arranged in the form of stumps reaching over each other in a cross bond, whereby the contoured elements and the corner-forming elements jointly take on the appearance of a massive blockhouse-type building mode, characterized in that
 - the contoured elements are designed to be mirror-symmetrical in their longitudinal extension and comprise near their respective front sides a transverse recess ~~each~~ for ~~the~~ contoured ~~element~~ elements positioned opposite ~~from them~~ one another to connect in the cross bond;
 - the corner-forming elements are designed in the form of round wood stumps with a cut surface that forms an end surface and comprise, on the opposite side, a first planar attachment surface and, adjacent to this and adapted to an external side of the crossing contoured element and corner-forming element a second attachment surface; and

- the contoured elements and the corner-forming elements provide a building kit for designing a ~~façade~~ facade for an external corner and an internal corner.

2. (Canceled).

3. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that the contoured elements, and the corner-forming elements, ~~and the intermittent parts~~ are connected to each other by means of plug-in connection elements.

4. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that at least two plug-in connection elements are provided at each site of connection between the contoured elements, and the corner-forming elements, ~~and the intermittent parts~~.

5. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that at least two bore holes for receiving the plug-in connection elements are provided at each site of connection of the contoured element ~~and the intermittent part~~.

6. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that the corner-forming elements each comprise in a left and right section of the first attachment surface at least two bore holes for receiving the plug-in connection elements.

7. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that the contoured element is designed as a semi-circular contour as seen in a cross-section that comprises a circular external side imitating a tree trunk and an attachment surface that is planar at least in part ~~and preferably comprises recesses~~.
8. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that the contoured element comprises in an upper section thereof and along its longitudinal extension a tongue and, on the opposite bottom side, a groove designed to be complementary in shape.
9. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that a fin surface is provided on the bottom side of the contoured element between an external side and a groove, whereby said fin surface and a contoured element that is assigned to and positioned adjacent to the fin surface form an overlapping area.
10. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or~~ 2, characterized in that the contoured element - as seen in a side view - comprises at each front side a circular segment-shaped milled recess that extends from a lower edge to the longitudinal middle plane and serves as second attachment surface and verges into a first planar attachment

surface that extends to the upper end of the contoured element.

11. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~ 5, characterized in that the bore holes are provided in the planar attachment surface of the contoured element.
12. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~, characterized in that the contoured element comprises in the second attachment surface near the first attachment surface a recess that extends transverse with respect to the longitudinal extension of the contoured element, whereby said transverse recess comprises a contour for receiving at least the tongue of a further contoured element that is arranged in the cross bond.
13. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~, characterized in that the corner-forming element consists of a round body that comprises on a bottom side thereof a concave surface whose radius of curvature preferably corresponds to the radius of the corner-forming element.
14. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~, characterized in that a planar cut surface is designed as the end surface of a trunk on a front side of the corner-forming element and in that the opposite front side, as seen in the lateral view, comprises in an upper half thereof a planar attachment surface that verges into a second attachment

surface that is formed by a circle segment-shaped milled recess whose radius of curvature preferably corresponds to the radius of the corner-forming element.

15. (Currently amended) ~~Façade~~ Facade according to claim 1, characterized in that the corner-forming element comprises a recess between a first attachment surface and a second attachment surface.
16. (Canceled).
17. (Canceled)
18. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~, characterized in that the contoured element comprises bore holes in the a transition area between the external side and the tongue, which bore holes are arranged to extend ~~obliquely~~ diagonally downward when viewed from outside to inside.
19. (Currently amended) ~~Façade~~ Facade according to claim 1 ~~or 2~~, characterized in that the contoured elements, and the corner-forming elements, ~~and the intermittent parts~~ are designed to be made from the wood of larch trees or Douglas firs for external areas and from the wood of pine trees, oak trees, northern firs, cedars, hemlock firs or as imitation

wood for internal areas.

20. (New) Facade according to claim 3, characterized in that the plug-in connection elements are made of wood or wooden dowels.